

Bollards



Nextage supplies and installs bollards across Australia along shopfront glass, entries, pickup bays and walkways, where a car nosing into a bay could reach the building or the people beside it. Steel bollards from 90 mm to 220 mm protect; flexible bollards guide traffic and spring back when hit. Our standard is a 90 mm galvanised steel post, 900 mm above ground, powder coated safety yellow with a reflective band. Our installed count is more than 2,000 bollards at more than 300 sites.

90 to 220 mm	Diameters, inground or bolted down
900 mm	Standard height above ground
3.5 mm	Standard galvanised steel wall
2 years	Warranty on the standard bollard

Our standard bollard

Material	Galvanised steel, 3.5 mm wall
Diameter	90 mm outside diameter
Length	1200 mm: 900 mm above ground, 300 mm below
Weight	12 kg
Finish	Powder coated safety yellow, reflective red band under a domed cap
Mounting	Core drilled and set into the ground
Warranty	Two years
Rating	Vehicle impact protection. Not a certified crash rated bollard

Other sizes, mountings and finishes are set on the site walk and written into the quote.

Every size, inground or bolted down

Diameter	Inground	Bolted down	Removable
90 mm, our standard	Yes	Yes	Yes
114 mm	Yes	Yes	Yes
140 mm	Yes	Yes	Yes
165 mm	Yes	Yes	Yes
220 mm	Yes	Yes	Yes
Other sizes	To order	To order	To order
Flexible, 450 to 900 mm high	No	Yes	Some models
Shock absorbing, 90 or 140 mm	No	Yes	No

Supplied and installed across Australia by Nextage Group. Call 1300 075 075 or ask for a quote at nextage.com.au/services/bollards-storefront-protection/inground-bollards/. Quotes within 2 business days.